



# Woodgrain Knotty Alder

Door Collection









Beauty
Strength
Durability



# **Knotty Alder Door Collections**

### 1-3/8" Thickness

The double hip raised panel profile offers a distinct 3/4" panel thickness that illuminates depth and design. Plank panel doors feature a v-groove, which offers the traditional beauty of tongue and groove construction without joint separation, swelling or rattling and create a flat panel, mission look. Both panel designs come standard with 3/4" Split Resistant Panels and Engineered stiles for greater stability. Shaker doors offer sharp, crisp lines that meet many designs trends and decors. We also offer the premium 1-1/4" thick panels in both raised "SRR" and plank "SRP" to compliment our 1-3/8" knotty alder offering.

#### **SPECIFICATIONS**

Height: 6'8", 8'0" | Thickness: 1-3/8" Width: 1/6, 2/0, 2/4, 2/6, 2/8, 3/0

All 1-3/8" designs include Express Ship stock of corresponding bi-folds





**KAL 102 PLK /** 102 DBH or SSR

\*stocked in 6/8 height only

KAL 802 PLK or SRP / 802 DBH or SRR\*

## **PANEL OPTIONS**















KAL 4102\*



KAL 4103\*



KAL 4103T\*



KAL 4107\*



**KAL 108 DBH\*** 

# 1-3/4" Thickness

The 1-3/4" doors provide both an inviting, welcome and a rich appearance. Both panel designs come standard with 1-3/8" thick Split Resistant Panels and engineered stiles for greater stability.

#### **SPECIFICATIONS**

Height: 6'8", 8'0" Thickness: 1-3/4" Width: 1/6, 2/0, 2/4, 2/6, 2/8, 3/0

- 802 & 102 designs in 1-3/4" include express ship stock of 20min fire doors.
- Any 1-3/4" Knotty Alder door can be made in 20 min, 60 min, & 90 min ratings

#### **PANEL OPTIONS**



1-3/8" SRR

3-1/4" Radius Raised Panel Design



Full Shoulder Plank Design



KAL 802 SRP / 802 SRR



KAL 102 SRP / 102 SRR