

Woodgrain's Super Step

Manufactured from 47# Industrial Particleboard. Engineered for interior Use only.

Description: An engineered composite wood product cut into standard widths and lengths with one long edge rounded for ease of carpet installation.

Specification Conformance: Physical and Mechanical Properties are averages from normal product runs.

Thickness Range: 1 1/8" Only

Woodgrain Particleboard complies with:

EPA TSCA Title VI, HUD 24 CFR 3280, CCR 93120 CARB ATCM Phase 2, CAN/CSA-0160-16 (Formaldehyde Emissions)
 ECC CPA 4-11 (Sustainability); ANSI A208.1 2016 (Physical Properties)
 Flame spread rating is class C (International Code Council – International Fire Code® and National Fire Protection Association 101 Life Safety Code®) as tested to ASTM E84 and CAN/ULC-S102-10.

Manufacturing Standards: Average	Imperial	Metric
Density	47.0 lb/ft ³	0.753 g/cm ³
Internal Bond	115 psi	0.793 N/ mm ²
Screw Hold - Face	310 lbs	1,379 N
Screw Hold - Edge	190 lbs	845.2 N
Formaldehyde, Emissions (TSCA Title VI)	< 0.09 ppm	< 0.09 ppm
Linear Expansion - Maximum	0.35%	0.35%
Water Absorption - Maximum	20%	20%
Moisture Content	7%	7%
Sanding	120 grit	-

Manufacturing Tolerances	Imperial	Metric
Thickness - Nominal	1 1/8 in	19.05 mm
Weight / MSF	4,433 lbs	±0.1016 mm
Packaging - Pieces per unit	56 pcs	±1.5875 mm
Width - Standard (inquire if spacial width required)	11 1/4 in	3.175 mm
Length - Standard (inquire if special length required)	8 ft, 10ft, 12ft	1.5875 mm

*Target value 0.005 under nominal

For more information, including sales terms and conditions:

Visit our website: Woodgrain.com

Send us an Email: ParticleboardSales@Woodgrain.com

Give us a Call: 888-264-7372

